



Data Security



Remote Upgrade



Breakpoint Retransmission



Pre-assembled, tested

## **Technical Parameter**

Basic Parameter	
Input Voltage	5V
Power	2W
Size (Length × Width × Tickness)	96±2mm × 49±2mm × 32±2mm
Operation Temperature Range	-30 ~ 60°C
Operation humidity	0 ~ 100% RH (No condensing)
Operation altitude	<4000m
Water Protection	IP65

Ethernet interface		
Port	RJ45	
Cable length	0.5m	
Waterproof level	IP65	
Commucation method	LAN&WiFi	

Software parameter		
Conguration	APP / WEB	
Language	English	
Transmitton speed	UART:115200bps Ethernet:10/100M adaptive	
Maximum transmission distance of a network cable	100m	
Operation mode	AP / STA / AP+STA	
Wireless standard	802.11 b/g/n	
Frequency Range	2.412GHz-2.484GHz	
Certication	CE / RCM	

## **Features**

- · Wi-Fi+LAN integrated into one, for centralized deployment and management simplified configuration & O&M
- · Data encrypted to ensure data security
- · Supports breakpoint retransmission automatic disconnection of broken links, reconnection and subsequent transmission to prevent data loss
- $\cdot$  Remote upgrade inverter program update without going on-site
- · Pre-assembled, tested and shipped no on-site installation required, stable performance