

SYN 50-XH-10

- Suitable for MIN-XH series inverters
- Support for power backup, up to 6kW
- Integrated breaker and meter, easy to install



GROWATT

www.ginverter.com

P O W E R
- I N G O
T O M O -
R R O W O

Datasheet	SYN 50-XH-10
Input From Grid	
Max. AC Input Overcurrent Protection	63A
Max. Continuous Input Current	50A
AC Output Voltage(Nominal)	230V
AC Output Voltage Range	180-270V
AC Frequency(Nominal)	50Hz/60Hz
AC Frequency Range	45-65Hz
Grid Disconnection Switchover Time	<500ms
Input From Inverter	
Rated AC Power	6000W
Max. Continuous Input Current@230V	26.1A
Rated AC Power in Continuous Backup Operation	6000W
Max. Continuous Input Current in Backup Operation	26.1A
Peak AC Power(<10s) in Backup Operation	6600W
Peak AC Current(<10s) in Backup Operation	28.7A
Additional Features	
Communication	RS485
Manual Control Bypass Switch	Yes
Energy Meter(for Import/Export)	1% accuracy
Cooling	Natural convection
Noise	<30dB
Operating Temperature Range	-40 °C ~60 °C
Protection Rating	IP65
Operating Humidity(RH)	Up to 100%
Maximum Elevation	3000m
Mounting options	Wall mounted
Weight	11kg
Dimensions(H/W/D)	365/450/123mm